

As the most technologically advanced Laser Screed® machine available in the world, the S-28EZ is packed with features that give you the competitive advantage.

Equipped with 360° machine rotation, a 25'/7.62m telescopic boom and your choice of pivoting screed heads, the S-28EZ continues the tradition of delivering the industry's highest quality and production rates with unsurpassed maneuverability. The customized OASIS laser control system is simple to operate and is upgradeable as technology advances. A redesigned, EZ Clean Head reduces clean-up time and improves long term maintenance. New easy access features improve ergonomics around the machine and operator efficiency.

The S-28EZ options platform allows you to build the machine you need to meet your demands. Options include, but are not limited to: 12' or 14' head width, roller plow, spray bar and the Somero® Floor Levelness System®.

**Contact us today at Sales@Somero.com / +61 3 9545 1778
or visit www.SOMERO.COM to learn more!**

FEATURES/BENEFITS:


**denotes new standard features*

- > Full Color LCD Display w/ Integrated Diagnostics
- > EZ Clean Screed Head*
- > Head Transport Stands*
- > Column-Block Protection
- > 360° Machine Rotation
- > Soft Landing
- > Hydraulic Screed Head Rotation
- > Hydraulic Pressure Washer (3,000 PSI/207 Bar) & Hose Reel*
- > Somero® Quick GradeSet System™
- > LED Work Lights & Compartment Lighting*
- > Built-In Storage
- > Automatic Throttle
- > Programmable Quick Pass
- > Illuminating Fuse Panel*
- > OASIS Laser Control System
- > Hydraulic Oil Pre-Heater
- > 4-Wheel & Crab Steering
- > Operator Heat

SPECIFICATIONS:

WEIGHT	17,880 lbs / 8,100 kg (with 12' / 3.7 m Screed Head)
WIDTH	7'3" / 2.2 m
HEIGHT	8' 9" / 2.67 m
LENGTH	31' 6" / 9.67 m (transport mode with 12' / 3.7 m screed head)
ENGINE	Kubota 74 Hp Stage 5 Engine
SELF-PROPELLED	Standard
SCREED HEAD WIDTH STANDARD OPTIONAL	14'5" / 4.4 m (15'5" / 4.7 m with flip down plow) 16'6" / 5.02 m (17'6" / 5.33 m with flip down plow)
VIBRATOR WIDTH STANDARD OPTIONAL	12' / 3.7 m 14' / 4.3 m

**Engine options & requirements vary based on location. Contact Sales for more information.*



OPTIONS:

- Floor Levelness System
- Spare Tire / Wheel Assembly
- Spare Auger Kit, 12'
- Spare Auger Kit, 14'
- Hub Caps
- Hydraulic Fitting Kit
- Spare Hydraulic Hose Kit
- Tripod Kit
- Column Clamp
- Umbrella Kit