



The S-15EZ Laser Screed® model is the newest addition to the Somero® EZ line of boom laser screed machines. Like its big brothers - the 22EZ and the 28EZ - this laser screed® machine comes with all of the time-saving and efficiency maximizing features that make the EZ Platform the best in the industry. These features include; Head Rotation with Proportional Control, Large Color Display, Joystick Control, Independent Auger and Vibrator Valves Speed Adjustment, and, of course, the EZ Clean Head.

From a productivity standpoint, It has a patented fully integrated self-leveling head assembly which plows, levels, and consolidates in just a single automated pass. The plow rakes down high concrete filling in low spots and the Somero® Quick Pass feature rakes down excessively high concrete without manual intervention. The hydraulically driven auger cuts the surface to grade and displaces excess concrete to the side via a double flight auger and the offset head design.

Our 20 ft / 6 m telescopic boom reaches out over the concrete allowing the operator to reach over chaired rebar and chaired mesh. Columns, pipes, box outs are no problem due to the ability to rotate around these obstacles while screeding. The S-15EZ is unique in the EZ line as it can be easily transported on a flatbed truck or tag-behind trailer.

**Contact us today at Sales@Somero.com / 1-239-210-6519
or visit www.SOMERO.COM to learn more!**

FEATURES/BENEFITS:

- > Improved Floor Quality & Increased Profitability
- > Somero® Quick GradeSet System™
- > OASIS Laser Control System
- > Column-Block Protection
- > 360° Machine Rotation
- > 2-Wheel, 4-Wheel, and Crab Steering
- > Full-time 4-Wheel Drive
- > Head Transport Stand

NEW FEATURES COMPARED TO S-15R

- Head Rotation with Independent Auger and Vibrator Valves Speed Adjustment
- Large - LCD display screen with diagnostics
- Joystick Control
- Oil Warmup Valve
- EZ Clean Head



SPECIFICATIONS:

WEIGHT (Nominal)	10,850 lbs / 4,921 kg (with 10' / 3.0 m Screed Head)
WIDTH	7'1" / 2.2 m
HEIGHT	7' / 2.13 m
LENGTH	24'6" / 7.5 m (transport mode)
ENGINE (STANDARD)	49.6 HP (37 kW) Kubota D1803 Turbo Diesel
BOOM LENGTH	20' (6.0 m)
SCREED HEAD WIDTH STANDARD OPTIONAL	11'6" / 3.51 m (Without Sonic Tracer) 8' / 2.4 m
VIBRATOR WIDTH	10' / 3.05 m

**Engine options & requirements vary based on location. Contact Sales for more information.*



OPTIONS:

- Lifting Sling
- Column Clamp
- Tripod
- Operator Comfort Package: Heated/Suspension Seat
- S-15R Silver Kit
- S-15R Gold Kit
- Spray Bar
- Auto Greaser
- Umbrella Kit
- RockTamp
- Spare Tire Kit
- Remote Telematic Machine Diagnostics (Proemion System)